FINAL REPORT MAY 1995

REPORT NO. 93-19

DOUBLE SECONDARY STEEL
CONTAINERS (SSCs) FOR
STORAGE OF LEAKING
M55 CHEMICAL ROCKETS

Approved for public release
Distribution Unlimited

19960827 104

Prepared for:

U.S. Army Armament, Munitions and Chemical Command ATTN: AMSMC-DSD-AS Rock Island, IL 61299-6000 Distribution Unlimited

DATO GRANGES EVALUATED)

VALIDATION ENGINEERING DIVISION SAVANNA, ILLINOIS 61074-9639

U.S. ARMY
ARMAMENT
MUNITIONS
CHEMICAL COMMAND

U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL

AVAILABILITY NOTICE

A copy of this report will be furnished each attendee on automatic distribution. Additional copies or authority for reprinting may be obtained by written request from Director, U.S. Army Defense Ammunition Center and School, ATTN: SMCAC-DEV, Savanna, IL 61074-9639.

DISTRIBUTION INSTRUCTIONS

Destroy this report when no longer needed. Do not return.

Citation of trade names in this report does not constitute an official endorsement.

The information contained herein will not be used for advertising purposes.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE

	F	REPORT DO	CUMENTATION	N PAGE				Approved 3 No. 0704-0188	
1a. REPORT SEC	URITY CLASSIFICA	TION		1b. RESTRICTIVE	1b. RESTRICTIVE MARKINGS				
UNCLA	SSIFIED								
2a. SECURITY CL	ASSIFICATION AUT	HORITY		3. DISTRIBUTION	/ AVAILABILITY OF	REPORT	.,,,,		
2b. DECLASSIFIC	ATION / DOWNGRA	DING SCHEDULE		UNLI	UNLIMITED 5. MONITORING ORGANIZATION REPORT NUMBER(S)				
4. PERFORMING	ORGANIZATION RE	PORT NUMBER(S)		5. MONITORING	ORGANIZATION RE	PORT NU	MBER(S)		
93-19									
6a. NAME OF PER			6b. OFFICE SYMBOL (if applicable)	7a. NAME OF MC	NITORING ORGANI	ZATION			
Center ar	y Defense An	imumuon	SMCAC-DEV						
6c. ADDRESS (Cit	y, State, and ZIP Cod	de)	SIVICAC-DE V	7b. ADDRESS (C	ity, State, and ZIP Co	de)			
i e	SMCAC-DEV	20							
8a. NAME OF FUN	IL 61074-963		8b. OFFICE SYMBOL	9 PROCUREMEN	NT INSTRUMENT ID	NTIFICAT	TION NUM	IRFR	
ORGANIZATIO	ON		(if applicable)	O. TROCORLINE	T MOTOMENT IS			.DEN	
	y Armament,		AMSMC-DSD-	AS					
	nical Comman		AMISMC-DSD-						
` '	y, State, and ZIP Cod	•		10. SOURCE OF PROGRAM	FUNDING NUMBERS PROJECT NO.	TASK NO	<u> </u>	WORK UNIT	
	AMSMC-DSD		ELEMENT NO.	, Modern Mod		•	ACCESSION NO.		
	nd, IL 61299-						·		
11. TITLE (Include	Security Classification	on)							
	-	l Containers (SSCs) for Storage	of Leaking M	155 Chemical	Rockets	S 		
12. PERSONAL AU William I									
13a. TYPE OF REI		13b. TIME COVER	FD	14 DATE OF PER	ORT (Veer Month I	David	15 DAGE	COUNT	
Final		14. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT 1995 May							
16. SUPPLEMENT	ARY NOTATION	FROM	TO	17731	······				
	COSATI CODES		18. SUBJECT TERMS (Continue on reverse	e if necessary and ide	ntify by bk	ck numbe	ri	
FIELD	GROUP	SUB-GROUP							
40 ABSTRACT (C									
19. ABSTRACT (C	onunue on reverse ir	necessary and idem	ту бу вюск питвег)						
The	U.S. Army De	efense Ammu	nition Center and	School (USA	DACS), Valid	ation E	ngineer	ring	
Division	(SMCAC-DE	V), was tasked	l by U.S. Army A	rmament, Mu	nitions and Ch	emical	Comm	and	
(AMCCC	M) to perform	n leak integrity	y tests on two SSO	Cs joined toge	ther. These te	sts wer	e condu	ıcted	
			inges so the two u						
			leaking M55 che						
conducte		1	3						
20. DISTRIBUTION	I / AVAII ARII ITV OF	ARSTRACT		21 APSTRACT S	ECURITY CLASSIFIC	CATION			
					SSIFIED	ALION			
UNCLASSIF		SAME AS RPT.	DTIC USERS		(Include Area Code)		220 05	FICE SYMBOL	
	H. KROHN			815-273		r	!	CAC-DEV	

DD Form 1473, Jun 86

Previous editions are obsolete

SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED

U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL VALIDATION ENGINEERING DIVISION SAVANNA, IL 61074-9639

REPORT NO. 93-19

DOUBLE SECONDARY STEEL CONTAINERS (SSCs) FOR STORAGE OF LEAKING M55 CHEMICAL ROCKETS

TABLE OF CONTENTS

P.	PART	PAGE NO.
1.	. INTRODUCTION	1-1
	A. BACKGROUND	1-1
	B. AUTHORITY	1-1
	C. OBJECTIVE	1-1
	D. CONCLUSION	1-1
2.	ATTENDEES	2-1
3.	. TEST PROCEDURE	3-1
4.	TEST ITEM	4-1
5.	. TEST RESULTS	5-1
6.	. PHOTOGRAPHS	6-1
7	DRAWINGS	7-1

INTRODUCTION

- A. <u>BACKGROUND</u>. The U.S. Army Defense Ammunition Center and School (USADACS), Validation Engineering Division (SMCAC-DEV), was tasked by U.S. Army Armament, Munitions and Chemical Command (AMCCOM) to perform leak integrity tests on two SSCs joined together. These tests were conducted following modification of the SSC flanges so the two units could be joined together. This approach was taken so multiple M55 rockets could be overpacked at one time versus the current procedure of Single Round Containers (SRCs) for each rocket. This container will not be used to overpack M55 rockets that are not already in a first overpack.
- B. <u>AUTHORITY</u>. This program was conducted IAW mission responsibilities delegated by the U.S. Army Armament, Munitions and Chemical Command (AMCCOM), Rock Island, IL.
- C. <u>OBJECTIVE</u>. The objective of these tests was to verify that the SSCs, following modification, could still maintain their leak integrity and be used as chemical storage overpack containers.
- D. <u>CONCLUSION</u>. All modified double SSCs had no detectable leaks in the 1 X 10⁻⁶ cc/he/sec/1.5 psi leak rate ranges with the exception of three containers (serial numbers 3117, 2544, and 3437), which had leak rates of 4 X 10⁻⁶ cc/he/sec/1.5 psi, 2 X 10⁻⁶ cc/he/sec/1.5 psi, and 2 X 10⁻⁶ cc/he/sec/1.5 psi, respectively. The maximum sensitivity of the tests conducted was 1 X 10⁻⁶ cc/he/sec/1.5 psi. All containers passed leak rate requirements for depot chemical storage containers.

30 NOVEMBER - 1 DECEMBER 1994

ATTENDEES

William R. Meyer

General Engineer

DSN 585-8090

815-273-8090

Bradley J. Haas

Mechanical Engineer

DSN 585-8336

815-273-8336

Director

U.S. Army Defense Ammunition Center

and School

ATTN: SMCAC-DEV

Savanna, IL 61074-9639

Director

U.S. Army Defense Ammunition Center

and School

ATTN: SMCAC-DEV

Savanna, IL 61074-9639

TEST PROCEDURE

Helium-leak tests were performed at 1.5 ± 0.5 psi with the use of a mass spectrometer and a sampling probe (referred to as the helium quick test). This test method has a maximum sensitivity of 1×10^{-6} cc/he/sec/1.5psi and was used due to the large physical size of the items being tested.

TEST ITEM

Two SSCs Joined Together

a. Height:	48.0 inches
b. Width:	33.3 inches
c. Length:	84.5 inches
d. Gasket:	butyl rubber
e. Torque on Flange Bolts:	30 ft-lbs.
f. Total Tested:	63 double SSCs

TEST RESULTS

A total of 63 double SSCs joined together were tested following modification. With the exception of three SSCs joined together (serial numbers 3117, 2544, and 3437), all containers had no detectable leaks. The three SSCs that did leak had leak rates of 4 X 10⁻⁶ cc/he/sec/1.5 psi, 2 X 10⁻⁶ cc/he/sec/1.5 psi, and 2 X 10⁻⁶ cc/he/sec/1.5 psi, respectively. It should be noted that the maximum sensitivity of the tests conducted was 1 X 10⁻⁶ cc/he/sec/1.5 psi; therefore, the true leak rate for all but the three containers listed above is not known. Table 1 below lists the serial number and leak rate for each container.

Table 1

Helium Leak Tests


Double SSC's

SSC	Leak Rate
Serial Number	cc/he/sec/1.5psi
0099	<1 X 10 ⁻⁶
0176	<1 X 10 ⁻⁶
0195	<1 X 10 ⁻⁶
0217	<1 X 10 ⁻⁶
0224	<1 X 10 ⁻⁶
0283	<1 X 10 ⁻⁶
0309	<1 X 10 ⁻⁶
0571	<1 X 10 ⁻⁶
0000	<1 X 10 ⁻⁶
0581	<1 X 10 ⁻⁶
0683	<1 X 10 ⁻⁶

SSC Serial Number	Leak Rate
Serial Number	cc/he/sec/1.5psi
0810	<1 X 10 ⁻⁶
0816	<1 X 10 ⁻⁶
0823	<1 X 10 ⁻⁶
0859	<1 X 10 ⁻⁶
1022	<1 X 10 ⁻⁶
1229	<1 X 10 ⁻⁶
1300	<1 X 10 ⁻⁶
1306	<1 X 10 ⁻⁶
1330	<1 X 10 ⁻⁶
1421	<1 X 10 ⁻⁶
1440	<1 X 10 ⁻⁶
1498	<1 X 10 ⁻⁶
1500	<1 X 10 ⁻⁶
1510	<1 X 10 ⁻⁶
1525	<1 X 10 ⁻⁶
1687	<1 X 10 ⁻⁶
1702	<1 X 10 ⁻⁶
1731	<1 X 10 ⁻⁶
1746	<1 X 10 ⁻⁶
1850	<1 X 10 ⁻⁶
1963	<1 X 10 ⁻⁶
1999	<1 X 10 ⁻⁶
2379	<1 X 10 ⁻⁶
2544	2 X 10 ⁻⁶
2571	<1 X 10 ⁻⁶
2583	<1 X 10 ⁻⁶
0000	<1 X 10 ⁻⁶


SSC	Leak Rate
Serial Number	cc/he/sec/1.5psi
2587	<1 X 10 ⁻⁶
2595	<1 X 10 ⁻⁶
2612	<1 X 10 ⁻⁶
2690	<1 X 10 ⁻⁶
2718	<1 X 10 ⁻⁶
2745	<1 X 10 ⁻⁶
2746	<1 X 10 ⁻⁶
2749	<1 X 10 ⁻⁶
2993	<1 X 10 ⁻⁶
0000	<1 X 10 ⁻⁶
2821	<1 X 10 ⁻⁶
2830	<1 X 10 ⁻⁶
2918	<1 X 10 ⁻⁶
3037	<1 X 10 ⁻⁶
3063	<1 X 10 ⁻⁶
3068	<1 X 10 ⁻⁶
3117	4 X 10 ⁻⁶
3135	<1 X 10 ⁻⁶
0000	<1 X 10 ⁻⁶
3215	<1 X 10 ⁻⁶
3270	<1 X 10 ⁻⁶
3423	<1 X 10 ⁻⁶
3437	2 X 10 ⁻⁶
4070	<1 X 10 ⁻⁶
4095	<1 X 10 ⁻⁶
6060	<1 X 10 ⁻⁶

PHOTOGRAPHS



U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL SAVANNA, IL

PHOTO NO. SCN95-122-1296: This photo shows the side view of a double SSC



U.S. ARMY DEFENSE AMMUNITION CENTER AND SCHOOL -SAVANNA, IL

PHOTO NO. SCN95-122-1297: This photo is a close up of the top flange and corner. Note guide pin for aligning SSC flanges during the joining process.

DRAWINGS

NOTES:

1. THE COUPLED ASSEMBLY OF SECONDARY STEEL CONTAINERS (SSC) USES TWO MODIFIED SSC BODIES. DORSN ARE DISCARDED, ONE GASKET WILL BE INSPECTED AND RETAINED FOR USE WITH THE COUPLED SSC AND THE SECOND GASKET WILL BE RETAINED FOR FUTURE USE. THE ORIGINAL 3708-24UMF DOLIS ARE DISCARDED.

94-03-04 SPR#5UE 94-03-08

LIM GENERAL CONTROLL TO THE TRANSPORT TO

- 2. REFER TO APPROPRIATE DRAWING FOR LOADING OF TOXIC CHEMICAL MANITIONS INTO THE LAKOUPLED CONTAINERS.
- 3. PLACE THE TWO HALVES TO BE ASSEMBLED ON FLOOR PLATE, PART NO ACVOOZ34-1 OR SIMILAR. THIS HELPS TO ALIGN THE TWO HALVES OVER THE TWO ALIGNING PINS IN ROCKH FLOOR ENVIRONMENTS AND REDUCES SLIDING FRICTION DURING ASSEMELY. RECOMMEND A 915 INCH STANDARD RAICHET BOX MERNH BE USED TO INITIALLY SNAG UP THE NAJIS (MCHASTER-CARR PART NO 5461A33).

Ø

SEE DETAIL 1


3/8-24UNF STUD ACV00231 (28 RE0D),

ALIGNMENT PIN ACVO0232 (2 RE00).

HEX FLANGE MJT 3/8-24 UNF SAE ,429 (28 REOD). IS/16 SC, CAPLUG

SS-DE4-B-4PH, -

- 4. SINIG UP THE MATS AT THE FLANGE TOP, 2 STOES AND UNDERNEATH AS FEACHABLE. LIFT THE CONTRINERS FIRM THE STOE BY FORKLIFT CENTERO ON THE FLANGE AREA. FORK THRES AT NAXIMAN SPREAD. PLACE SAFETY STAND, PART NO ACVORDS—1 UNDER THE CONTRINENT. RECOWERS USINE A 9/15 INCH RATICHE BOX FROW FOOT NERKEN, LOZ INCH DRIVE, PART NO ACVORDS—1 ASSEMBLE TO A 1/2 DRIVE WERCH FOR THE FOLLOWING TORDUE OPERATIONS. STARTING AT THE LOWER LEFT CORNER AND NOVING CLOCKATISE, TORROW EVERT NOT TO 300 INCH-POUND. TORRUE SEQUENCE A SECORD THE.
 - 5. THE CONTAINER SHALL BE EXAMINED AND TESTED IN ACCORDANCE NITH DNG ACVOO233, METHOD 1.
- 6. ALL EXTRAIOR PAINTED SURFACES SHALL BE TOXCH-UP PAINTED IN ACCORDANCE WITH DMG ACZOGOGOA23, HASK SWACELOK PRIOR TO PAINTING, AFTER PAINTING, REHOVE HASKING TAPE AND INSTALL CAPLUG.
- 7. INTERIOR SURFACES SHALL BE FREE OF OIL OR DIRT.
- 8. FOR SERIAL NUMBER MARKING REQUIREMENTS, SEE DETAIL 1.



PART NO ACVM0230-1

TACK WELD PART NO. ACWRO230-4 NEXT TO PART NO. ACWRO230-2.

FOR ACWRO230-2.

FART NO. ACWRO230-4 IS TO USE THE SAME NAVERIC NUMBER FOUND ON ACWRO230-2.


FOR A MATCHEO SET.


DETAIL 1

DETAIL 1

1/2 SCALE

DISTRIBUTION STATEMENT A, UNLIHITED






94-03-04 | SPRAGUE APPROVED SHEET 4 OF ARMAMENT WINITIONS AND CHEMICAL COMMAND DEFENSE AMMUNITION CENTER AND SCHOOL SAVANNA, ILLINOIS 61074-9639 PART NO ACVM0230-4 ACVM0230 SAME SECONDARY STEEL CONTAINER, COUPLED DATE THE NUMERIC NUMBER TO BE THE AS THE NUMBER APPEARING ON MATCHED PART NO ACVMO230-2 RELEASED FOR PRODUCTION UNIT WT REVISION DESIGN ACTIVITY 28620 CAGE CODE SCALE 1-1/2 DESCRIPTION 9/16 SIZE 2 JHK THOMAS J MICHELS SUBSTITED

CHEF, LOSISTICS ENGINEERING OFFICE
APPROVED BY OFFICE OF COMMODING COMMODING
APPROVED BY OFFICE
A SPRAGUE U.S. ARMY DEFENSE AMARITION CENTER AND SCHOOL 0374 WILLIAM F ERNST CHECKER PROJENGA 94-01-10 TH 2 3/8 REF MIO DETSHE 1. MATERIAL: 12 GA (1046) HOT OR COLD ROLLED SHEET STEEL.
2. SERIAL NUMBER "SVADA XXXX" SHALL BE APPLIED BY METAL STAMP
1/4 INCH HIGH TO A DEPTH THAT WILL BE LEGIBLE AFTER PAINTING. SVADA 3.0 BREAK UNLESS OTHERWISE NOTED
DIMENSIONS ARE IN INCHES.
SHARP CORNERS AND EOGES.
TOLERWICES ON ± 1/16 FRAC ! IONS INDICATES THE DEPOT DOING THE MODIFICATION HATERIAL DECIMALS ANGLES USED ON APPLICATION ACVM0230-3 NEXT ASSY DISTRIBUTION STATEMENT A, UNLIMITED NOTES:

3/8-24 UNF X 2 INCH LENGTH, RIGHT HAND THREAD LENGTHS AS SHOWN, GRADE 8 (150,000 PSI MINIMUM TENSILE STRENGTH), PER SAE J429, CADMIUM PLATED PER 00-P-416, TYPE II CLASS 2 THREAD. NOTES:

	REVISION		
LTR	DESCRIPTION	DATE	APPROVEO
1	RELEASED FOR PRODUCTION	94-03-04 SPRAGUE	SPRAGUE
X	XA CORRECT SPELLING ERROR	94-03-08	
_		_	



PART NO ACV00231-1

		UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES. BREAK	94-01-10		DESIGN ACTIVITY	U.S. ARMY	
		SHARP CORNERS AND EDGES.	DETSHI CHECKER PROJ ENGR	PROJ ENGR	AHMAMENI,	MUNITIONS AND CHEMILAL LUMMAND	
		TOLERANCES ON		SPRAGIE	SAV	SAVANNA, ILLINOIS 61074-9639	
		FRACTIONS #1/16		700111			7
		- SIZETINAL S	SHCAC-DEV	i i	į		_
		+	- J-K-I HOMA;	JEK THOMAS J MICHELS		SIUD, 3/8-24UN-,	
		AMOLES	CHIEF, SUP	HIEF, SUPPLY ENGINEERING DIV	Č	יווודט אטייטיון	_
			SUBMITTED				
		MAIEHIAL	MILLIAM F FRNST	FBNST	Ĭ		
			CHIEF, LOGISTICS ENGINEERING OFFICE	INEERING OFFICE		LUNIAINEH, LUUPLEU	
			APPROVED BY OFIDER OF CO	MHANDING			Τ
 ACVM0230-2			GENERAL, U.S. JAHY MATERIEL COMMO (AMC) SIZE CAGE CODE	HIEL COMMUNO (ANC)	SIZE CAGE CODE		
 NEXT ASSY	NO OBSO		WILLIAM F ERNST	EPINST	B 28620	ALVUUZ31	
							_
 APPL I(APPLICATION		U.S. ARHY DEFENSE AMACHITION CENTER AND SCHOOL		SCALE 2 UNIT WT	UNIT WT SHEET OF	

DISTRIBUTION STATEMENT A, UNLIMITED

SPRAGUE SPRAGUE SHEET | OF U.S. ARMY
ARMAMENT, MUNITIONS AND CHEMICAL COMMAND
DEFENSE AMMUNITION CENTER AND SCHOOL
SAVANNA, ILLINOIS 61074-9639 PART NO ACV00232-ALIGNMENT PIN, 3/8-24UNF, SECONDARY STEEL ACV00232 CONTAINER, COUPLED 94-03-04 94-03-08 94-03-16 SEE NOTE UNIT WT XA CORRECT SPELLING ERRORS XB CHANGED DIAMETER TO .50 RELEASED FOR PRODUCTION **REVISION** DESIGN ACTIVITY 28620 CAGE CODE DESCRIPTION SCALE SIZE 8 SYCKE-DEV THOMAS J MICHELS CHIEF SUPPLY ENGINEERING DIV SUB-11TED

OHER. LOGISTICS BASINEEMED OFFICE
PROPED IS. SAMY WIERIEL COM-WIC (ANC.) SPRAGUE DEFENSE APPLAITION CENTER AND SCHOOL - 1/16 WILLIAM F ERNST 5/8 CHECKER PROJENCA 94-01-10 OIW DETSYN DATE 2 3/4 BREAK 2/8 UNLESS OTHERWISE NOTED DIMENSIONS ARE IN INCHES. SHARP CORNERS AND EDGES. 1/16 1,005 1045, MEDIUM CARBON, COLD FINISH ROUND 50 TOLERANCES ON FRACT 10NS DECIMALS HATERIAL ANGLES . USED ON SCREW DRIVER SLOT, 1/16 X 1/8 DEEP APPL ICATION 3/8-24 UNF, RIGHT HAND THREAD. ACVM0230-2 NEXT ASSY DISTRIBUTION STATEMENT A, MATERIAL: BAR STOCK. UNLIMITED

TEST METHOD I

- 1. COMPLETE THE APPROPRIATE TOROUE SEQUENCE FOR THE CONTAINER
- 2. CONNECT HELIUM SOURCE TO SWAGELOCK, IF INSTALLED, OR INSTALL SCHPAEDER VALVE TO MAKE THE CONNECTION.
- 3. PRESSURIZE CONTAINER TO 5 ± 1 PSI WITH HELTUM
- 4. USE MASS SPECTROWEIER WITH OUICK TEST PROBE TO CHECK ALL WELDS, AND FLANGE JOINTS TO INCLUDE AREA AROUND BOLISSYSUOS. RECORDED LEKK RATE NOT TO EXCEED IX 10°4 CUBIC CENTIMETERS HELLUM PER 3 ATMOSPHERES PER SECOND (1 X 10°4 cc He/.3Atm/Sec) GR THE LEKK RATE REQUIREMENTS OF THE CONTAINER.
- CONTAINERS EXCEEDING THE LEAK RATE IN STEP 4 SHALL HAVE THE LEAK POINT(S) IGENTIFIED FOR REPAIR.
- 6. AFTER REPAIR, CONTAINER WILL BE RE-IESTED IN ACCORDANCE WITH STEPS 1-4 ABOVE. THE HELLUM FROM THE PREVIOUS TEST HUST HAVE DISPERSED INTO THE SUMBOLADING AIR BEFORE AN ACCURATE READING CAN BE OBTAINED ON ANY NEW TEST.
- 7, IF A SCHAREDER VALVE WAS INSTALLED; REMOVE SCHRAEDER VALVE AND INSTALL A PIPE PLUG IN ACCORDANCE WITH NOTE 1.

TEST METHOD II

- COMPLETE THE APPROPRIATE TOROUE SECUENCE FOR THE CONTAINER.
- 2. CONNECT THE VACULM PUMP IMLET HOSE INTO A PLUG ON THE TEST SAMPLE.
- 3. BLOCK THE TEST CONTAINER A FOOT OFF THE FLOOR VITH THE CONTAINER OVERHANGING THE BLOCKTING.
- 4. EVACUATE THE CONTAINER TO 0 ATMOSPHERE.
- 5. COVER THE CONTAINER WITH PLASTIC SKEETING DIAPING ON ALL 4 SIDES AND HELD AT THE FLOOR LINE BY A ROPE ON OTHER SUITABLE HEANS TO FORM A COMPLETE INMERTED BAG. INSURE THE PLASTIC IS WITHOUT HOLES.
- ADMIT HELIUM INTO THE BAG AT THE BOTTON UNTIL THE BAG STARTS TO EXPAND LIKE A BALLOON (TEST SPECIMEN SURBOUNDED BY A HELIUM RICH ATMOSPHERE).
- 7. HONITOR THE EXHAUST OF THE VACUAN PUMP WHICH HAS BEEN CONTINUOUSLY RUNNING SINCE STEP 4. THE RECORDOLLEK RATE IS NOT TO EXCEED I X 10° COBIC CENTENDIRES HELLUN PER AMMOSPHER PER SECOND (1 X 10° CC HEA/ARZE) OR HEL LEKK RATE REQUIREMENTS OF THE CONTAINER. THE HONITORING THE END OF STEP 6.
 - CONTAINERS EXCEDING LEAK RATE AT STEP 7 WILL BE REMOVED FROM THE INVERTED PLASTIC BAG AND LEAK POINTS IDENTIFIED FOR REPAIR BY 1EST METHOD 1.
- 9. AFTER REPAIR, THE CONTAINER WILL BE RE-TESTED IN ACCORDANCE WITH STEPS 1-7 ABOVE.
- 10. REMOVE THE VACUUM HOSE FROM TEST SAMPLE AND INSTALL A PIPE PLUG IN ACCORDANCE WITH NOTE 1.

TEST METHOD 11

94-03-04 SPRAGUE 94-03-08

DELEASED FOR PRODUCTION REVISE NOTE 3, NETHOO 11


- I. COMPLETE THE APPROPRIATE TOROUE SEQUENCE FOR THE CONTAINER
- 2. INSTALL SCHRAEDER VALVE
- 3. PRESSURIZE CONTAINER TO (2 ATM ± 0.5 PSI) WITH HELIUM.
- 4. VENT CONTAINER TO 1 ATMOSPHERE
- 5. PLACE CONTAINER INTO A VACUUM CHAMBER
- 6. REDUCE PRESSURE IN VACUUM CHAMBER TO D ATMOSPHERE.
- . THE RECONDED LEAK RATE IS NOT 10 EXCEED 1 X 10° CUBIC CENTINETERS HELIUM PER ATMOSPHERE PER SECOND (1 X 10° CC He/Atm/Sec) OR THE LEAK RATE REDUIREMENTS OF THE CONTAINER.
- 8. CONTAINERS EXCEEDING LEAK RATE AT STEP 7 VILL BE REHOVED FROM THE TEST CHAMBER AND LEAK POINTS IDENTIFIED FOR REPAIR BY TEST WETHOO I.
 - 8. AFTER REPAIR, THE CONTAINER VILL BE RE-TESTED IN ACCORDANCE VITH STEPS 1-7 ABOVE.
 - IO. FENOVE SCHRECCER VALVE AND INSTALL PIPE PLUG IN ACCORDANCE WITH NOTE 1.

NOTES:

TO INSTALL PIPE PLUG AFTER TESTING, SEAL THE PLUG WITH ANTISEIZE (TEFLON) TAPE, MIL-1-27730. WRAP TAPE, 1-1/2 TO 2 TIPES AROUND THREADS COUNTERCICKNISE (TE LOOKING AT PLUG FAD) OR CLOCKNISE (TE LOOKING AT PLUG FAD). INSTALL PIPE PLUG AND TOROXE TO SO-75 INCH-PORNUS.

94-01-10 We will be to be the transfer of the	DIW SPRAGUE SAVANN, ILLINOIS 61974-9639		OSS. MAN DISTINCT CONTROL TRUCKSON	IN E FORT I I I I I I I I I I I I I I I I I I I	OVERPACK CONTAINERS	Marie and a comment comment of 12 DIG COG COG	VILLIAM FERNST D 28820 ALVUUZ33	1 20 1 222
RE IN INDEE. INCA.	AIG		-	MIRIA. VIII	110 200	The state of the s	MILL	
							HEXT ASSY USED ON	APPLICATION
	•	_!	1		•			DISTRIBUTION STATEMENT A, UNLIMITED

DESTON ACTIVITY




ASSEMBLED PART NO ACVOC235-1 PRIMARY DESIGN; SINGLE PIECE DESIGN ACTIVITY


U.S. AND GENERA COMMON

DESIGN ANALITY COMMON

STANMAL, ILLINOIS 01074-9039 ACV00235 BOTTOM PAN, SECONDARY STEEL CONTAINER, COUPLED - RELEASED FOR PRODUCTION 28,85 28.70 94-01-10 00 01V SPRAGUE H3.05 H VILLIAN F EPRIST
ONE, MILLIAN FORMANCE STEEL
MANUAL W.L. ANT MIRITAL COPING 1862 WILL TAM F EPNST DALIS SACIAL WITH DIGITAL SACK DIGITAL SACIAL SACIA APPL1CATION ACVM0230-1 82.97, SEE NOTE 4 -- CENTER OF BEND; 4 SIDES 86.87, SEE NOTE 4 -.85.85 - 90.05 -SPAK THE 4 TOP EDGES AS SHOW AND FORM INTO PAN. THE SPANKED DINENSION IS THE RESULTANT MATERIAL LEFT AFTER FORMING FROM 36 INCH WIDTH SHEET (EVENLY DIVIDED). 1. NATERIAL: 14 GA (.0247), 36 INCH VIDTH, ASTM-A3GG, LOW CARBON, COMMERCIAL GUALITY, COLO ROLLEO SHEET STEEL. CALCULATED DIMENSIONS CENTER 10 CENTER OF BENDS BASED ON 1/16 RADIUS INSTOE BEND. CALCULATED DIMENSIONS ARE SHOWN; SEE SHEET 4 OF 4 FOR FINISHED TOLERANCES. DETAIL, 2, SEE NOTE 3 FULL SCALE - CENTER OF BEND SEE NOTE 3 1 DISTRIBUTION STATEMENT A, UNLIMITED 28.92 NOTE 4 32.82 NOTE 4 NOTES:





94-03-04 SPRAGUE ASSEMBLED PART NO ACYOO235-1 ALTERNATE DESIGN; 3 PIECE SHEET 4 OF 4 BOTTON PAN,
SECONDARY STEEL
CONTAINER, COUPLED
B 28620 A FLIC APLIFIER U.S. ANN APLIFUL CONVO CEPTION APLIFUL CONVO CEPTION AND CEPTION AND SCHOOL SAVARUM, ILLINGIS 61074-9638 ACV00235 1716171 - 4 SEE NOTE 4 RELEASED FOR PRODUCTION REVISION 94-01-10
01Y
10XX
1 HIGHS
1 HI WILLIAM F EPNST CUT-A-WAY VIEW, ASSEMBLED PART NO ACVO0235-1 UMISS THE STATE WITH THE STATE SEE NOTE 3 1716 T E # SEE NOTE 2 APPLICATION ACVM0230-1 83.0 1.25 PART NO ACY00235-3, I REOD, SEE NOTE 1; ESTIMATED FLAT = 4.75 X 28.85, 2.9 POUNDS 28,85 OR 10 FIT SPARK THE FOUR TOP EDGES AS SHOWN. THE SPARKED DIMENSION IS THE RESULTANT MATERIAL. LEFT AFTER FORMING PART NO ACVOOZ35-2 FROM 36 INCH WIDTH SHEET (EVERLY DIVIDED). USE THE SAME SPARKED DIMENSION FOR PART NO ACVOOZ35-3. 1, MATERIAL: 14 GA (.0247), 36 INCH VIDTH, ASTH-A366, LOW CARBON, COMMERCIAL OUALLIY. COLO ROLLED SHEET STEEL. .075 EACH END THE ENDS ARE TO BE FULL WELDED AT ALL JANCTIONS ON THE INSIDE FOR NO LEAKS (WATER TEST). PART NO ACVO0235-2, I RECO, SEE NOTE 1; ESTIMATED FLAT = 36 X 83, 64.2 POUNDS SEE HOTE 2 REL IEVE CORNER, 2 2 PLACES £ 29.0 ±.125 ~ DISTRIBUTION STATEMENT A, UM. IMITED 4. TACK WELD ENDS AT DUTSIDE SEE NOTE 2 2.0 4.125 NOTES: ∻ m





. .

,










1/2 X 9/16 STANDARD RATCHET BOX WRENCH McMASTER-CARR PART NO 5461A33



CAD FILE \SSC\WRENCH-1.PRT

